



BTE-132

Category
Mechanical /
maintenance

Capacity
2 passengers

Configuration

Bed

- With a vise
- With configurable storage compartments (shelves and drawers)
- With an inverter and 120V (AC) outlets
- Spare tire support
- Made of aluminum

Front cab

- Closed
- Heated
- With A/C (optional)
- FOPS Level 2 (optional)
- FOPS/ROPS Level 2 (optional)

DESCRIPTION

This model is perfectly configured for various trades working in the field that require extensive tools and/or spare parts. The BTE-132 provides great autonomy and flexibility to these workers, enhancing their efficiency. Based on the BTE-128, this model does not include air conditioning.

PRE-MODIFICATIONS SPECIFICATIONS

Model code	HZJ79, 4WD
-------------------	------------

TO LEARN MORE ABOUT THIS MODEL

Contact us and we can guide you through the next steps and the selection of your options.

Capacity	1 t
Engine	1HZ 6 cylinder (CANMET certified #949)
Torque	207 lb-ft @ 4000 RPM
Transmission	5-speed manual (R151)
Factory front brakes	Disc brakes (322 X 32 mm)
Factory rear brakes	Drum brakes (295 mm)
Factory tires	7.50 x 16, 8-ply rating, off-road, mounted on 1-piece rims
Gross vehicle weight rating (GVWR)	3,200 kg (7,054 lbs)
Front gross axle weight rating (GAWR)	1,460 kg (2,866 lbs)
Rear gross axle weight rating (GAWR)	2,300 kg (5,071 lbs)
Factory front suspension	Coil springs
Factory rear suspension	Semi-elliptical leaf springs
Steering	Power assisted recirculating ball
Towing capacity	750 kg (1,650 lbs) or 3,500 kg (7,700 lbs) with trailer brakes
Length	220 in
Width	84 in

705 419-2602

landcruiser@acces-s.ca



Daniel

Shawn



