



BTE-300

Category
Man carrier

Capacity
3 passengers (5 total)

Configuration

Rear cab

- Closed
- With cargo space
- Spare tire support
- Made of aluminum

Front cab

- Closed
- Heated
- With A/C (optional)
- FOPS Level 2 (optional)
- FOPS/ROPS Level 2 (optional)

DESCRIPTION

The BTE-300 model offers an ideal setup for transporting workers and equipment to specific work sites. It provides great versatility and comfort, especially for mining sites with colder conditions due to its enclosed rear cabin. If you are interested in this configuration, be sure to check out the new double-cab model.

PRE-MODIFICATIONS SPECIFICATIONS

Model code	HZJ79, 4WD
Capacity	1 t
Engine	1HZ 6 cylinder (CANMET certified #949)
Torque	207 lb-ft @ 4000 RPM
Transmission	5-speed manual (R151)

TO LEARN MORE ABOUT THIS MODEL

Contact us and we can guide you through the next steps and the selection of your options.

705 419-2602

landcruiser@access-s.ca

Factory front brakes	Disc brakes (322 X 32 mm)
Factory rear brakes	Drum brakes (295 mm)
Factory tires	7.50 x 16, 8-ply rating, off-road, mounted on 1-piece rims
Gross vehicle weight rating (GVWR)	3,200 kg (7,054 lbs)
Front gross axle weight rating (GAWR)	1,460 kg (2,866 lbs)
Rear gross axle weight rating (GAWR)	2,300 kg (5,071 lbs)
Factory front suspension	Coil springs
Factory rear suspension	Semi-elliptical leaf springs
Steering	Power assisted recirculating ball
Towing capacity	750 kg (1,650 lbs) or 3,500 kg (7,700 lbs) with trailer brakes
Length	220 in
Width	84 in

