



BTE-306

Category

Man carrier

Capacity

3 passengers (5 total)

Configuration**Rear cab**

- Closed
- Insulated (Superior insulation with acoustic panels or urethane)
- FOPS/ROPS Level 2 certified
- With cargo space
- Spare tire support
- Made of aluminum

Front cab

- Closed
- Heated
- With A/C (optional)
- FOPS/ROPS Level 2 certified

DESCRIPTION

Very similar to the BTE-300 model, the Toyota Land Cruiser BTE-306 stands out with its FOPS/ROPS certification for both cabins. Its enclosed rear design makes it ideal for colder conditions. It retains its ease in transporting workers and equipment, combining versatility and comfort.

PRE-MODIFICATIONS SPECIFICATIONS

Model code	HZJ79, 4WD
Capacity	1 t

TO LEARN MORE ABOUT THIS MODEL

Contact us and we can guide you through the next steps and the selection of your options.

705 419-2602

landcruiser@acces-s.ca

Engine	1HZ 6 cylinder (CANMET certified #949)
Torque	207 lb-ft @ 4000 RPM
Transmission	5-speed manual (R151)
Factory front brakes	Disc brakes (322 X 32 mm)
Factory rear brakes	Drum brakes (295 mm)
Factory tires	7.50 x 16, 8-ply rating, off-road, mounted on 1-piece rims
Gross vehicle weight rating (GVWR)	3,200 kg (7,054 lbs)
Front gross axle weight rating (GAWR)	1,460 kg (2,866 lbs)
Rear gross axle weight rating (GAWR)	2,300 kg (5,071 lbs)
Factory front suspension	Coil springs
Factory rear suspension	Semi-elliptical leaf springs
Steering	Power assisted recirculating ball
Towing capacity	750 kg (1,650 lbs) or 3,500 kg (7,700 lbs) with trailer brakes
Length	220 in
Width	84 in



Daniel

Shawn





