



BTE-306

Category
Man carrier

Capacity
3 passengers (5 total)

Configuration

Rear cab

- Closed
- Insulated (Superior insulation with acoustic panels or urethane)
- FOPS/ROPS Level 2 certified
- With cargo space
- Spare tire support
- Made of aluminum

Front cab

- Closed
- Heated
- With A/C (optional)
- FOPS/ROPS Level 2 certified

DESCRIPTION

Very similar to the BTE-300 model, the Toyota Land Cruiser BTE-306 stands out with its FOPS/ROPS certification for both cabins. Its enclosed rear design makes it ideal for colder conditions. It retains its ease in transporting workers and equipment, combining versatility and comfort.

PRE-MODIFICATIONS SPECIFICATIONS

| | |
|-------------------|------------|
| Model code | HZJ79, 4WD |
| Capacity | 1 t |

TO LEARN MORE ABOUT THIS MODEL

Contact us and we can guide you through the next steps and the selection of your options.

705 419-2602

landcruiser@access-s.ca

| | |
|--|--|
| Engine | 1HZ 6 cylinder (CANMET certified #949) |
| Torque | 207 lb-ft @ 4000 RPM |
| Transmission | 5-speed manual (R151) |
| Factory front brakes | Disc brakes (322 X 32 mm) |
| Factory rear brakes | Drum brakes (295 mm) |
| Factory tires | 7.50 x 16, 8-ply rating, off-road, mounted on 1-piece rims |
| Gross vehicle weight rating (GVWR) | 3,200 kg (7,054 lbs) |
| Front gross axle weight rating (GAWR) | 1,460 kg (2,866 lbs) |
| Rear gross axle weight rating (GAWR) | 2,300 kg (5,071 lbs) |
| Factory front suspension | Coil springs |
| Factory rear suspension | Semi-elliptical leaf springs |
| Steering | Power assisted recirculating ball |
| Towing capacity | 750 kg (1,650 lbs) or 3,500 kg (7,700 lbs) with trailer brakes |
| Length | 220 in |
| Width | 84 in |





