



BTE-600

Category
Man carrier

Capacity
6 passengers (8 total)

Configuration

Rear cab

- Closed
- Insulated
- Heated
- FOPS/ROPS Level 2 certified
- Two rows of three passengers facing forward
- Storage under the rear seat accessible from the outside
- Made of aluminum

Front cab

- Closed
- Heated
- With A/C (optional)
- FOPS/ROPS Level 2 certified

DESCRIPTION

The Toyota Land Cruiser BTE-600 aims to provide a more comfortable solution for workers by orienting the seats forward. It remains well-suited for mines operating under constant cold conditions.

PRE-MODIFICATIONS SPECIFICATIONS

Model code	HZJ79, 4WD
Capacity	1 t
Engine	1HZ 6 cylinder (CANMET certified #949)

TO LEARN MORE ABOUT THIS MODEL

Contact us and we can guide you through the next steps and the selection of your options.

705 419-2602

landcruiser@access-s.ca

Torque	207 lb-ft @ 4000 RPM
Transmission	5-speed manual (R151)
Factory front brakes	Disc brakes (322 X 32 mm)
Factory rear brakes	Drum brakes (295 mm)
Factory tires	7.50 x 16, 8-ply rating, off-road, mounted on 1-piece rims
Gross vehicle weight rating (GVWR)	3,200 kg (7,054 lbs)
Front gross axle weight rating (GAWR)	1,460 kg (2,866 lbs)
Rear gross axle weight rating (GAWR)	2,300 kg (5,071 lbs)
Factory front suspension	Coil springs
Factory rear suspension	Semi-elliptical leaf springs
Steering	Power assisted recirculating ball
Towing capacity	750 kg (1,650 lbs) or 3,500 kg (7,700 lbs) with trailer brakes
Length	220 in
Width	84 in



