



## BTE-800

**Category**  
Man carrier

**Capacity**  
8 passengers (10 total)

### Configuration

#### Rear cab

- Closed
- Insulated
- Heated
- With storage compartments under the seats, accessible via foldable seats
- Made of aluminum

#### Front cab

- Closed
- Heated
- With A/C (optional)
- FOPS Niv. 2 (optionnel)
- FOPS/ROPS Niv. 2 (optionnel)

## DESCRIPTION

The Toyota Land Cruiser BTE-800, just as durable, shares the same setup as the BTE-815 model. Providing a more cost-effective option, it doesn't have FOPS/ROPS certifications but remains specialized in personnel transport under constant cold conditions.

## PRE-MODIFICATIONS SPECIFICATIONS

<b>Model code</b>	HZJ79, 4WD
<b>Capacity</b>	1 t
<b>Engine</b>	1HZ 6 cylinder (CANMET certified #949)

## TO LEARN MORE ABOUT THIS MODEL

Contact us and we can guide you through the next steps and the selection of your options.

705 419-2602

landcruiser@acces-s.ca

<b>Torque</b>	207 lb-ft @ 4000 RPM
<b>Transmission</b>	5-speed manual (R151)
<b>Factory front brakes</b>	Disc brakes (322 X 32 mm)
<b>Factory rear brakes</b>	Drum brakes (295 mm)
<b>Factory tires</b>	7.50 x 16, 8-ply rating, off-road, mounted on 1-piece rims
<b>Gross vehicle weight rating (GVWR)</b>	3,200 kg (7,054 lbs)
<b>Front gross axle weight rating (GAWR)</b>	1,460 kg (2,866 lbs)
<b>Rear gross axle weight rating (GAWR)</b>	2,300 kg (5,071 lbs)
<b>Factory front suspension</b>	Coil springs
<b>Factory rear suspension</b>	Semi-elliptical leaf springs
<b>Steering</b>	Power assisted recirculating ball
<b>Towing capacity</b>	750 kg (1,650 lbs) or 3,500 kg (7,700 lbs) with trailer brakes
<b>Length</b>	220 in
<b>Width</b>	84 in



