



BTE-823

Category
Man carrier

Capacity
8 passengers (10 total)

Configuration

Rear cab

- Split box
- Closed
- Insulated
- Heated
- FOPS/ROPS Level 2 certified
- With storage compartments accessible under the foldable seats
- Made of aluminum

Front cab

- Closed
- Heated
- With A/C (optional)
- FOPS/ROPS Level 2 certified

DESCRIPTION

The BTE-123 model, having the same configuration as the BTE-815, is equipped with a detachable box, allowing it to be taken underground in several pieces without the need for cutting. Once underground, the vehicle can be quickly reassembled while maintaining its FOPS/ROPS certification, which is impossible with other models. This solution is ideal for mining sites with a narrow mine shaft. In fact, the entire vehicle, including the front cabin, is designed to be disassembled and reassembled underground. Just like the BTE-815, its rear cabin, which is enclosed, insulated, and heated, is perfectly suited for cold conditions.

PRE-MODIFICATIONS SPECIFICATIONS

Model code	HZJ79, 4WD
-------------------	------------

TO LEARN MORE ABOUT THIS MODEL

Contact us and we can guide you through the next steps and the selection of your options.

705 419-2602

landcruiser@acces-s.ca

Capacity	1 t
Engine	1HZ 6 cylinder (CANMET certified #949)
Torque	207 lb-ft @ 4000 RPM
Transmission	5-speed manual (R151)
Factory front brakes	Disc brakes (322 X 32 mm)
Factory rear brakes	Drum brakes (295 mm)
Factory tires	7.50 x 16, 8-ply rating, off-road, mounted on 1-piece rims
Gross vehicle weight rating (GVWR)	3,200 kg (7,054 lbs)
Front gross axle weight rating (GAWR)	1,460 kg (2,866 lbs)
Rear gross axle weight rating (GAWR)	2,300 kg (5,071 lbs)
Factory front suspension	Coil springs
Factory rear suspension	Semi-elliptical leaf springs
Steering	Power assisted recirculating ball
Towing capacity	750 kg (1,650 lbs) or 3,500 kg (7,700 lbs) with trailer brakes
Length	220 in
Width	84 in



