



BTE-905

Category
Mine rescue

Capacity
8 passengers (10 total)

Configuration

Rear cab

- Closed
- Insulated
- Heated
- Made of aluminum
- With a 120V (AC) inverter to plug in work tools
- With smart chargers for the starter battery, auxiliary battery, and inverter battery
- With storage compartments accessible under the foldable seats
- With storage shelves for medical and other equipment
- With storage and brackets for stretchers
- With auto-eject outlets that activate when the engine starts
- With a rearview camera
- With a night vision camera
- With a thermal imaging camera (optional)
- With gas detectors (CO, NO₂, etc.)
- With emergency/fire flashing lights and beacons
- With a siren and intercom (optional)
- With a fire safety system (optional)
- With an LED bar (optional)

Front cab

- Closed
- Heated
- With A/C (optional)
- FOPS Level 2 (optional)
- FOPS/ROPS Level 2 (optional)
- With detachable front seat backs for driving with an oxygen tank (optional)

DESCRIPTION

The BTE-905 is our most advanced mining rescue vehicle, designed for operations in extreme conditions. Equipped with thermal and night vision cameras, it ensures safe navigation even in darkness. Its detachable front seat backs allows driving with an oxygen tank. The heated and insulated rear cabin provides all the necessary amenities for transporting the injured. Auto-eject outlets and smart chargers ensure the vehicle is immediately ready for use, crucial when every second counts. Many options can be added or removed according to your needs.

PRE-MODIFICATIONS SPECIFICATIONS

Model code	HZJ79, 4WD
Capacity	1 t
Engine	1HZ 6 cylinder (CANMET certified #949)
Torque	207 lb-ft @ 4000 RPM
Transmission	5-speed manual (R151)
Factory front brakes	Disc brakes (322 X 32 mm)
Factory rear brakes	Drum brakes (295 mm)
Factory tires	7.50 x 16, 8-ply rating, off-road, mounted on 1-piece rims
Gross vehicle weight rating (GVWR)	3,200 kg (7,054 lbs)
Front gross axle weight rating (GAWR)	1,460 kg (2,866 lbs)
Rear gross axle weight rating (GAWR)	2,300 kg (5,071 lbs)
Factory front suspension	Coil springs
Factory rear suspension	Semi-elliptical leaf springs
Steering	Power assisted recirculating ball
Towing capacity	750 kg (1,650 lbs) or 3,500 kg (7,700 lbs) with trailer brakes
Length	220 in
Width	84 in

TO LEARN MORE ABOUT THIS MODEL

Contact us and we can guide you through the next steps and the selection of your options.

705 419-2602

landcruiser@access-s.ca









