



## BTE-914

**Category**  
Mine rescue

**Capacity**  
4 passengers (6 total)

### Configuration

#### Rear cab

- Open
- Roofless
- With storage compartments accessible under the foldable seats
- With storage and straps for stretchers
- With a ladder (optional)
- With a double rear bumper to facilitate cab access
- With emergency/fire flashing lights and beacons
- With an LED bar (optional)
- Made of aluminum

#### Front cab

- Closed
- Heated
- With A/C (optional)
- FOPS Level 2 (optional)
- FOPS/ROPS Level 2 (optional)

## DESCRIPTION

The BTE-914 is one of our mining rescue models designed for operations in less extreme conditions, requiring less specialized equipment. It allows for quick response when needed, and numerous options can be added according to your specific requirements.

## PRE-MODIFICATIONS SPECIFICATIONS

<b>Model code</b>	HZJ79, 4WD
<b>Capacity</b>	1 t

## TO LEARN MORE ABOUT THIS MODEL

Contact us and we can guide you through the next steps and the selection of your options.

705 419-2602

<b>Engine</b>	1HZ 6 cylinder (CANMET certified #949)
<b>Torque</b>	207 lb-ft @ 4000 RPM
<b>Transmission</b>	5-speed manual (R151)
<b>Factory front brakes</b>	Disc brakes (322 X 32 mm)
<b>Factory rear brakes</b>	Drum brakes (295 mm)
<b>Factory tires</b>	7.50 x 16, 8-ply rating, off-road, mounted on 1-piece rims
<b>Gross vehicle weight rating (GVWR)</b>	3,200 kg (7,054 lbs)
<b>Front gross axle weight rating (GAWR)</b>	1,460 kg (2,866 lbs)
<b>Rear gross axle weight rating (GAWR)</b>	2,300 kg (5,071 lbs)
<b>Factory front suspension</b>	Coil springs
<b>Factory rear suspension</b>	Semi-elliptical leaf springs
<b>Steering</b>	Power assisted recirculating ball
<b>Towing capacity</b>	750 kg (1,650 lbs) or 3,500 kg (7,700 lbs) with trailer brakes
<b>Length</b>	220 in
<b>Width</b>	84 in



